	Product Information	Manufacturer	CNP
	Product information	Address	Yuhang District, Hangzhou, Zhejiang,
COND	100WQ100-29-15H(I)	Contact	86-571-88637351
	1004/Q100-53-12U(1)	Date	2022/03/09
Project Name	ama		DPA
Project Name		Client Addr.	
Item NO		Contacts	Alireza
ILEIII NO		Contact	

Item NO			Contacts	Alireza
		Contact		
Part NO. 100V	VQ100-29-15H			
Product Picture Note				
		The sewage submersible pu the pump. The two are separated by a Divided into fixed automati	n oil chamber and	a mechanical seal assembly.
technology				
Pump rotator speed	1440			
Nameplate standards	CE			
Material				
Impeller	HT200			
Pump shaft	20cr13			

#### Installation

Rubber code Pump case

Connection Code F

Maximum Pressure/Temperatu 6bar/40

Flange Standard DIN

Pressure Class PN6

Р

HT200

# Medium

Medium Temperature40Maximum diameter of partic55Maximum Environment Temper40

# Structure dimension

Standard caliber DN
Outlet Diameter DN100

# Motor

Number of Motor Phase Three Phase **Protection Class** IP68 Insulation Class F Motor Power 15 **Power Frequency** 50HZ Rated Voltage (V) 380V Rated Current (A) 30.6 Starting mode direct boot


#### Seal

Mechanical Seal H-50

#### Others

Weight (kg) 270


	Performance Curve	Manufacturer	CNP
	renormance curve	Address	Yuhang District, Hangzhou, Zhejiang,
COND	100WQ100-29-15H(I)		86-571-88637351
	10044(100-29-13H(1)	Date	2022/03/09
Project Name	Droject Name		DPA
Project Name		Client Addr.	
Item NO		Contacts	Alireza
Itell NO		Contact	



	Pump Technical Parameters	Manufacturer	CNP
	Fullip recliffical Farameters	Address	Yuhang District, Hangzhou, Zhejiang,
COND	100WQ100-29-15H(I)	Contact	86-571-88637351
	10044/00-53-121(1)	Date	2022/03/09
Project Name		Client Name	DPA
Project Name		Client Addr.	
Item NO		Contacts	Alireza
ILEITINO		Contact	

Rated parameters	
Pump model	100WQ100-29-15H(I)
Part NO.	100WQ100-29-15H
Rated flow (m³/h)	100
Rated head (m)	29
Rated efficiency (%)	63
Power (kW)	12.54
NPSHr (m)	2
Speed (rpm)	1440

Medium	
Pumped medium	Clean Water
Working temperature (°C)	20
Medium density (kg/m³)	1000
Viscosity (mm²/s)	1
	<u> </u>






	Structure picture	Manufacturer	CNP
	Structure picture	Address	Yuhang District, Hangzhou, Zhejiang,
COND	100WQ100-29-15H(I)	Contact	86-571-88637351
CIAL	10044(100-53-121(1)	Date	2022/03/09
Project Name		Client Name	DPA
Project Name		Client Addr.	
Item NO		Contacts	Alireza
item NO		Contact	

# **CNP** Nanfang Zhongjin Environment Co., Ltd.

SECTIONAL DRAWING		No.	No	•
TYPE submers	sible sewage pump	MODE	L WQ-1	1/15kW



No.	names of parts	number	material	No.	names of parts	number	material
1	cable	1	YZW	20	casing	1	HT200
6	cable sleeve	1	HT200	21	impeller	1	HT200
50	top cover	1	HT200	26	framework oil seal	1	NBR-2
58	cable transit board	1	Q235	140	oil filler plug	2	SUS304
64	base	1	HT200	36	machine oil 32#		(11)
25	mechanical seal	1	Carbon/SIC	52B	lower bearing	2	
60	lower cover	1	HT200	56	stator	1	100
30	oil lift	1		55	rotor	1	- 430 T
46	Air release bolt	1		54	shaft	1	70 V.
94	guiding	1	HT200	52A	upper bearing	1	
92	pipe	1	SUS304 (unaffiliated)	72	eye bolt	2	SUS304
93	guide hook	1	HT200	510	lift chain	1	45#(forging galvanized)
91	water outlet base	1	HT200	23	foot bracket	3	HT200
22	water inlet cover	1	HT200	10	Cable lockblock	2	HT200

Nanfang Zhongjin Environment CO.,LTD.

unit: mm

	Installation picture	Manufacturer	CNP
	ilistaliation picture	Address	Yuhang District, Hangzhou, Zhejiang,
COND	100WQ100-29-15H(I)	Contact	86-571-88637351
	100000100-29-1311(1)		2022/03/09
Project Name		Client Name	DPA
Project Name		Client Addr.	
Item NO		Contacts	Alireza
Item NO		Contact	

