	Product Information	Manufacturer	CNP
	Product information	Address	Yuhang District, Hangzhou, Zhejiang,
COND	CDLK1-120/12	Contact	86-571-88637351
	CDLK1-120/12	Date	2022/07/17
Project Name		Client Name	DPA
		Client Addr.	
Item NO		Contacts	Alireza
		Contact	

Part NO.	1100055647	
Product Picture	•	Note
		Product introduction CDLK/CDLKF is non-self priming multi-stage centrifugal pump installed with standard motor. The motor shaft is directly connected with the pump shaft through coupling. The impellers and diffusers are made of stainless steel plate stamping and welding. In order to meet the requirement of installation depth of the water tank or vessel, it is possible to install cavity diffusers for changing length of the pump. Performance and advantages Compact structure Convenient maintenance Changeable installation depth
technology		<u> </u>

Nameplate standards Material

Pump rotator speed

Impeller 304
Rubber code P
Material Code S

2900

CE

Medium

Medium Temperature normal-15+70Medium Temperature high t-15+105Maximum Environment Temper40

Motor

Number of Motor Phase
Protection Class
IP55
Insulation Class
Motor Power
O.75KW
Power Frequency
Rated Voltage (V)
Rated Current (A)
Energy Efficiency Level
Three Phase
Three Phase
Three Phase
Three Phase

20/380

3.1/1.8A


Seal

Mechanical Seal CDL-12/WSF14

Others

Weight (kg) 20


	Performance Curve	Manufacturer	CNP	
	renormance curve	Address	Yuhang District, Hangzhou, Zhejiang,	
COND	CDLK1-120/12	Contact	86-571-88637351	
	CDLK1-120/12	Date 2022/07/17	2022/07/17	
Project Name		Client Name	DPA	
		Client Addr.		
Item NO		Contacts	Alireza	
		Contact		



	Pump Technical Parameters	Manufacturer	CNP	
	rump reclinical rataliteters	Address	Yuhang District, Hangzhou, Zhejiang,	
COND	CDLK1-120/12	Contact	86-571-88637351	
	CDLK1-120/12	Date	2022/07/17	
Project Name		Client Name	DPA	
		Client Addr.		
Item NO		Contacts	Alireza	
		Contact		


Rated parameters			
Pump model	CDLK1-120/12		
Part NO.	1100055647		
Rated flow (m³/h)	1		
Rated head (m)	67		
Rated efficiency (%)	36		
Power (kW)	0.51		
NPSHr (m)	2		
Speed (rpm)	2900		
Max impeller diameter (mm)	75		

Medium	
Pumped medium	Clean Water
Working temperature (°C)	20
Medium density (kg/m³)	1000
Viscosity (mm²/s)	1





	Structure picture	Structure picture Manufacturer CNP	CNP
	Structure picture	Address	Yuhang District, Hangzhou, Zhejiang,
COND	CDLK1-120/12	Contact	86-571-88637351
CIAL	CDLK1-120/12	Date	2022/07/17
Project Name	Client Name	DPA	
	Client Addr.		
Item NO		Contacts	Alireza
		Contact	



	Dimension Drawing	Manufacturer	CNP	
	Difficusion Drawing	Address	Yuhang District, Hangzhou, Zhejiang,	
COND	CDLK1-120/12	Contact	86-571-88637351	
CIAL	CDLK1-120/12	Date 2022/07/17	2022/07/17	
Project Name		Client Name	DPA	
		Client Addr.		
Item NO		Contacts	Alireza	
		Contact		

