<b>A</b>	Product Information	Manufacturer	CNP
		Address	Yuhang District, Hangzhou, Zhejiang,
CNP	CDLK42-100/10	Contact	86-571-88637351
DOI W	CDLK42-100/10	Date	2022/07/19
Project Name		Client Name	DPA
		Client Addr.	
Item NO		Contacts	Alireza
		Contact	

Part NO.	1100057338			
Product Picture		Note		
S.C.		Product introduction  CDLK/CDLKF is non-self priming multi-stage centrifugal pump installed with standard motor. The motor shaft is directly connected with the pump shaft through coupling. The impellers and diffusers are made of stainless steel plate stamping and welding. In order to meet the requirement of installation depth of the water tank or vessel, it is possible to install cavity diffusers for changing length of the pump.  Performance and advantages  Compact structure Convenient maintenance Changeable installation depth		

# Nameplate parameters

flow 42 m³/h
head 203 m
Efficiency 71
speed 2900
number of stages 10

# technology

Pump rotator speed 2900 Nameplate standards CE

# Material

Impeller304Rubber codePMaterial CodeS

#### Medium

Medium Temperature normal -15°C+70°C

Medium Temperature high t -15°C+105°C

Maximum Environment Temper 40°C

Three Phase

#### Motor

Number of Motor Phase

Protection Class IP55
Insulation Class F
Motor Power 37KWKW
Power Frequency 50HZ
Rated Voltage (V) 380V
Rated Current (A) 68.3A
Energy Efficiency Level IE3


# Seal

Mechanical Seal CDLA-22/WSF14

### Others

Weight (kg) 320


	Performance Curve	Manufacturer	CNP
		Address	Yuhang District, Hangzhou, Zhejiang,
CNP	CDLK42-100/10	Contact	86-571-88637351
DOI W	CDLK42-100/10	Date	2022/07/19
Project Name		Client Name	DPA
		Client Addr.	
Item NO		Contacts	Alireza
		Contact	



	Pump Technical Parameters	Manufacturer	CNP
Tump recimical raidineters	Tamp redimed rarameters	Address	Yuhang District, Hangzhou, Zhejiang,
CONP	CDLK42-100/10	Contact	86-571-88637351
DOI W	CDLK42-100/10	Date	2022/07/19
Project Name		Client Name	DPA
		Client Addr.	
Item NO		Contacts	Alireza
		Contact	

Rated parameters			
Pump model	CDLK42-100/10		
Part NO.	1100057338		
Rated flow	42 m³/h		
Rated head	203 m		
Rated efficiency (%)	71		
Power (kW)	32.7		
NPSHr (m)	3		
Speed (rpm)	2900		
Max impeller diameter (mm)	136		
	·		

Medium	
Pumped medium	Clean Water
Working temperature (°C)	20
Medium density (kg/m³)	1000
Viscosity (mm²/s)	1





	Physical picture  CDLK42-100/10	Manufacturer	CNP
		Address	Yuhang District, Hangzhou, Zhejiang,
CNP		Contact	86-571-88637351
D OIT		Date	2022/07/19
Project Name		Client Name	DPA
		Client Addr.	
Item NO		Contacts	Alireza
		Contact	

